



NOTES


- 1. Gasket and groove may be in the seat or underside of cover.
- 2. For bolt down manhole ring and covers that are not designated "Watertight", the neoprene gasket, groove and washer are not required.
- 3. Washer shall be neoprene (Detail "B").
- 4. In lieu of blind pick notch for storm sewer manhole covers, drill three 1" diameter holes at 120° spacing.
- 5. Proprietary manhole covers without bottom ribs are acceptable.
- 6. For clarity, the vertical scale of the Cover Section has been exaggerated, it is 1.5 times the horizontal scale (1H:1.5V).



BOLT ON CAM TYPE LOCKING DEVICE DETAIL "C"

SKID GROOVE PATTERN DETAIL





BOLT ON CAM TYPE LOCKING DEVICE

(c)**SECTION**

MANHOLE RING AND COVER STANDARD PLAN B-25

SHEET 1 OF 1 SHEET

APPROVED FOR PUBLICATION

Harold J. Peterfeso 06-30-04



NOTE: THIS PLAN IS NOT A LEGAL ENGINEERING DOCUMENT BUT AN ELECTRONIC DUPLICATE.
THE ORIGINAL, SIGNED BY THE ENGINEER AND APPROVED FOR PUBLICATION, IS KEPT ON FILE
AT THE WASHINGTON STATE DEPARTMENT OF TRANSPORTATION. A COPY MAY BE OBTAINED UPON REQUEST.